


CHAPTER 6 - ACCESSORIES

6.1 12 V / 24 V CHARGERS




6.1.1 Description

This charger is for use in a car (or truck) only. The adapter is fitted with a cigar lighter type connector. AC1 is used to charge a mobile on a cigar lighter connector.

6.1.2 Characteristics

Item	Packaging reference	Input voltage	No load voltage	Output current	Comments
CIGAR LIGHTER CHARGER AC1	Blister	10.8 to 30 V=	6.5 V	500 mA	

6.2 DESKTOP CHARGERS AND CRADLES




6.2.1 Description

This charger could charge a mobile, while acting as holder the handset.

6.2.2 Characteristics

Item	Designation	Nature
1	SIMPLE DESKTOP CRADLE	Simple support recess

6.3 CAR CRADLE



6.3.1 Description

Car cradle compatible with AC1 or antenna adapter.

6.3.2 Characteristics

Item	Packaging	Comments
CAR CRADLE KIT mechanical	BLISTER	Mechanical craddle


6.4. FULL DUPLEX CAR HANDSFREE KIT

6.4.1. Description

Rapido Kit : "compact" kit on cigar lighter,
K3 Kit : "confort" kit for integration in car with phone equipment.

6.4.2. Characteristics

Item	Packaging	Comments
Rapido kit	Box	No antenna.




A : Connecting case and loudspeaker.

B : Cradle.

C, D et E : Support kit.

F : Microphone.

Item	Packaging	Comments
K3 KIT	Box	No antenna. Requires car installation 900/1800 MHz dual band



1 : Loudspeaker.

2 : Cradle.

3 : Microphone.

4 : Connecting case.


5 : Power supply cable.

6 : Cable : microphone, loudspeaker, car \leftrightarrow connecting case.

7 : Cable : mobile \leftrightarrow connecting case.

8 : Support kit.

6.5 PEDESTRIAN HANDSFREE KIT



6.5.1 Description

Ear support with microphone on the cable for handsfree conversation.

6.5.2 Characteristics

Item	Dimensions	Loudspeaker impedance	Microphone
PEDESTRIAN HANDSFREE KIT	Length: 1.25 m Dist. micro/loudspeaker: 25 cm	150 Ω 119 dB SPL	2,2 k Ω -42 dB SPL

6.6 DATA CABLES

6.6.1 Description

Data cables are used for transferring data through standard equipment.

6.6.2 Characteristics

Item	Packaging	Target mobile	Mobile link to	Signals
DATA CABLE	Blister	Range 900/3000/myX- 3/myX-5	PC	Standard V28 3V<Us<-3V Fmax = 115kbauds
DATA CABLE	Blister	myX-5/ myX 1-2	PC	